





GEOKRETE-CR

RAPID SETTING HIGH EARLY STRENGTH CONCRETE RESURFACING MORTAR

INTRODUCTION

-  GEOKRETE-CR is a proprietary blend of powders based on geopolymer technology used for repair and rehabilitation / re-surfacing of horizontal concrete surfaces.
-  It has been specifically formulated to produce superior bond strength coupled with a quick setting and high early strength gain that allows the repaired surfaces to be used or opened to traffic within a short period of time.

KEY FEATURES



**QUICK
SETTING**



**CURING
FREE**



**HIGH
STRENGTH**



**ACCEPTS
TRAFFIC AS
EARLY AS 2
HOURS**

OTHER INFORMATION

Flexural Strength	7 MPa
Shrinkage	None
Open Porosity	Less than 1%
Unit Weight	2100 kg/m ³



USES/APPLICATIONS

- Concrete Roads/highways
- Industrial Floors
- Parking Garages
- Bridge Decks
- Airport Runways, Freezer Floors

cemeco® Natural Cemeco Private Limited

📍 Near Jhota Farm, Gudli, Teh.-Mavli, Dis.- Udaipur, Rajasthan, 313024

📍 506-507, Neelkanth 1, Bhawani Singh Road, Jaipur (Raj.) 302001

☎ +91 7229808081, +91 9549367999

✉ info@cemeco.in 🌐 www.cemeco.in



Navoday Sciences Private Limited

📍 No. 12, First Floor- A, Race View Colony, 3rd Street, Guindy, Chennai, Tamil Nadu – 600032

✉ info@navodaysciences.co.in

🌐 www.navodaysciences.co.in



Disclaimer : These instructions and recommendations define the material and the method of use but cannot be considered as a substitute for the skills, training and qualifications of the contractor. In addition to these recommendations, the requirements of the building/road regulations, the recommendations of the appliance manufacturer and general health & safety considerations may be applicable. The company guarantees the quality of the products but has no control over the way in which the products are used. If there is any doubt the customer is advised to carry out his own trials of the materials before starting the work.