

THERMAGROUT-W

WATER PROOF TILE JOINT GROUT

INTRODUCTION

- Advanced Geopolymer based - contains no portland cement
THERMAGROUT is an un-sanded tile joint grout.
- It is a pre blended mixture of inorganic polymers, natural minerals and selective pigments.
- To impart a completely watertight joint apart from providing hard, uniformly colored, abrasion, mild acids and detergents resistant joints with greater adhesion and compression strength.

KEY FEATURES



QUICK
SETTING



HIGHLY
IMPERMEABLE
TO WATER



HIGH
STRENGTH



WALKABLE IN
2 HOURS



OTHER INFORMATION

Colour	White & Grey
Flexural Strength	4-5 MPa
Water Absorbtion	<2.0%
Wet Density	2.0 g/cm ³
Working Time	10 Minutes at 30°C


USES/APPLICATIONS

-  Floor tile
-  Ceramic tiles
-  Cement tiles
-  Terrace tiles
-  Bathroom tiles





cemeco[®] Natural Cemeco Private Limited

 Near Jhota Farm, Gudli, Teh.-Mavli, Dis.- Udaipur, Rajasthan, 313024


 506-507, Neelkanth 1, Bhawani Singh Road, Jaipur (Raj.) 302001


 +91 7229808081, +91 9549367999

 info@cemeco.in  www.cemeco.in



Navoday Sciences Private Limited

 No. 12, First Floor- A, Race View Colony, 3rd Street, Guindy, Chennai, Tamil Nadu – 600032

 info@navodaysciences.co.in

 www.navodaysciences.co.in



Disclaimer : These instructions and recommendations define the material and the method of use but cannot be considered as a substitute for the skills, training and qualifications of the contractor. In addition to these recommendations, the requirements of the building/road regulations, the recommendations of the appliance manufacturer and general health & safety considerations may be applicable. The company guarantees the quality of the products but has no control over the way in which the products are used. If there is any doubt the customer is advised to carry out his own trials of the materials before starting the work.