



rapidfloor-m

SELF LEVELING OVERLAYMENT/UNDERLAYMENT

INTRODUCTION

-  RAPIDFLOOR is a single component proprietary blend of powders based on Microcrystalline technology mixed with graded sand that is water activated.
-  It is used as underlayment to provide a smooth surface which can accept various floor covering including wood, vinyl sheet and carpet as little as 24 hours.

KEY FEATURES



**QUICK
SETTING**



**HIGH EARLY
STRENGTH**



**WALKABLE
IN
3 HOURS**



**ACCEPT
FLOOR
COVERING IN
24 HOURS**

OTHER INFORMATION

Splitting Tensile Strength in 28 Days	3.5 MPa
Shrinkage	None
Open Porosity	Less than 1%
Unit Weight	2170 kg/m ³
Flexural Strength in 24 hours	6 MPa

USES/APPLICATIONS

- Rapidfloor is used to level floors to provide flat and smooth surface prior to installing ceramic tile, carpet, resilient flooring, athletic floors, wooden parque etc
- Can be installed for a thickness ranging from 3 mm to 50 mm. For applications requiring more than 10mm thickness Rapidfloor can be extended with clean aggregates.



Natural Cemeco Private Limited

- Plot No.: 2-5, Shree Marble Nagar, Behind Sukher Police Station, Sukher, Udaipur (Raj.) 313001
- 506-507, Neelkanth 1, Bhawani Singh Road, Near 22 Godam Puliya C Scheme, Jaipur (Raj.) 302001
- +91 9549367999, +91 7229808081
- pallavi@cemeco.in  www.cemeco.in



Navoday Sciences Private Limited

- No. 12, First Floor- A, Race View Colony, 3rd Street, Guindy, Chennai, Tamil Nadu – 600032
- Old No.73 New No.26, , Five Furlong Road, Guindy, Chennai, Tamil Nadu, 600032
- info@navodaysciences.co.in
- www.navodaysciences.co.in

